

Test Report

No.: 64.190.25.4251.01-00

Dated: 2025-08-28



Applicant: ALSANIT sp. z o. o.
Address: ul. Wielenska 2, 64-980 Trzcianka, POLAND
Sample Submission: The samples were submitted by applicant and identified.
Product Name: Office Chair
Order No.: /
Identification/Style No.: ELEPHANT
Manufacturer: /
Country of Origin: /
Export to: /
Receipt Date of Sample: 2025-04-24
Date of Testing: From 2025-04-25 to 2025-05-19
Test Result: Refer to the data listed in following pages

Test Specification(s) or Test Item(s):

1. EN 1335-1:2020+A1:2022 Office furniture—Office work c6hair—Part 1: Dimensions—Determination of dimensions

Conclusions:

Pass

Hardline Laboratory

TÜV SÜD Certification and Testing (China) Co., Ltd. Guangzhou Branch



Tested By:

Knight Li

Knight Li

Test Engineer

Reviewed By:

Rookie Wen

Rookie Wen

Designated Reviewer

Note:

- (1) The TÜV SÜD Certification and Testing (China) Co., Ltd. "General Terms & Conditions" applied. Any use for advertising purposes must be granted in writing. This technical report may only be quoted in full. This report is the result of a single examination of the object in question. It does not imply a general statement regarding the quality of products from regular production. For further details please see "Testing, Certification, Validation and Verification Regulations", chapter A-3.3. For full version, please visit: EN : <https://www.tuvsud.cn/zh-cn/resource/terms-and-conditions---en> ; SCN: <https://www.tuvsud.cn/zh-cn/terms-and-conditions> ; TCN: <https://www.tuvsud.com/zh-tw/terms-and-conditions>
- (2) The results relate only to the Items tested.
- (3) The test report shall not be reproduced except in full, without the written approval of the laboratory.

Laboratory:
B1/F. of Building A2, Building D1, No.63,
Chuangqi Road, Shilou, Panyu District,
Guangzhou, Guangdong, China 511447

Telephone : +86 20 3832 0668
Telefax : +86 20 3832 0478
<https://www.tuvsud.com>

Regd. Office:
TÜV SÜD Certification and Testing (China) Co.,
Ltd. Guangzhou Branch 5F, Communication
Building, 163 Pingyun Rd, Huangpu West Ave.
Guangzhou 510656P.R. China

Page 1 of 7

Description of the test subject:

1	Product Description	Office Chair
2	Dimensions / Weight	H x W x D (mm): 1125~1367 x 745 x 715 Weight (kg): 19.7
3	Intended use	Office use

Sample photo(s)





Sample preparation: the sample was stored in indoor ambient conditions for 24h
 Test condition: 23°C 53%RH

Test Results:

1. EN 1335-1:2020+A1:2022 Office furniture—Office work chair—Part 1: Dimensions—Determination of dimensions

Clause	Requirement -Test	Measuring result- Remark	Verdict
7	Measurement methods and procedures The chair shall be set up as specified in ISO 24496:2021, 6.2.1. The CMD shall be placed in the chair as specified in ISO 24496:2021, 6.2.2 and 6.2.3 The chair dimensions shall be determined in the sequence specified in Table 1.		
8	Dimensional requirements	Dimension measured was based on Type B data	/
Table 2—Dimensional requirements			
a	Seat height and sitting height	Seat height: 416~520mm Sitting height: 411~515mm	P
b	Adjustable depth of the seat	409~465mm	P
	Fixed depth of the seat	Adjustable seat	N/A
f	Adjustable height of lumbar support	160~270mm	P
	Fixed height of lumbar support	Adjustable lumbar support	N/A
q	Maximum distance from the backrest to the front of the armrests	304mm	P
r	Hip breadth clearance when armrests are in widest position	540mm	P
z	Adjustable clear distance between armrest	443~530mm	P
	Fixed clear distance between armrest	Adjustable armrests	N/A
p	Height of armrests adjustable	211~288mm	P
	Height of armrests not adjustable	Adjustable armrests	N/A
d	Seat pad width	490mm	P
c	Seat pad depth	410mm	P
h	Backrest height	622mm	P
j	Backrest width	384mm	P
k	Radius of backrest	552mm	P
n	Armrest length	235mm	P
o	Armrest width	101mm	P
s	Offset of the underframe	384mm	P
Table 3—Angle requirements			
γ	Angle between seat and back	96.1°~112.9°	P
l	Backrest inclination range	31.6°	P
e	Seat pad angle adjustable	-0.6°~-11.4°	P
	Minimum adjustment range	10.8°	P
	Seat pad angle fixed	-0.6°	P
9	Information for use	Fulfilled	P
Annex C Dimensions for neck rests and headrests			
x	Height of adjustable neck rest or head rest	597~703mm	P
	Height of fixed neck rest or head rest	Adjustable neck rest or head rest	N/A



Table 2—Dimensional requirements

Table 2 — Dimensional requirements

Dimensions in millimetres

Dimensions in millimetres

		Type Ax					Type A					Type B					Type C				
		Allow (-)	Min.	Max.	Allow (+)	Minimum range	Allow (-)	Min.	max.	Allow (+)	Minimum range	Allow (-)	min.	max.	Allow (+)	Minimum range	Allow (-)	min.	max.	Allow (+)	Minimum range
<i>a^{ab}</i>	Seat height and sitting height ^c	yes	400	540	yes	160	yes	400	520	yes	130	yes	420	510	yes	100	yes	430	480	yes	80
<i>b</i>	Adjustable depth of the seat	yes	380	430	yes	70	yes	425	450	yes	70	yes	425	445	yes	50	yes	425	-	yes	-
	Fixed depth of the seat	no					no					no	425	485	no	fixed	no	425	-	yes	fixed
<i>f</i>	Adjustable height of lumbar support	yes	170	300	yes	Minimum 70 within the range	yes	170	300	yes	Minimum 70 within the range	yes	170	300	yes	Minimum 50 within the range	yes	170	300	yes	-
	Fixed height of lumbar support	no					no					no	170	300	no	-	no	170	300	no	-
<i>q^d</i>	Maximum distance from the backrest to the front of the armrests	yes	-	200	no	-	yes	-	300	no	-	yes	-	350	no	-	yes	-	400	no	-

		Type Ax					Type A					Type B					Type C				
		Allow (-)	Min.	Max.	Allow (+)	Minimum range	Allow (-)	Min.	max.	Allow (+)	Minimum range	Allow (-)	min.	max.	Allow (+)	Minimum range	Allow (-)	min.	max.	Allow (+)	Minimum range
<i>r^e</i>	Hip breadth clearance when armrests are in widest position	no	480	-	yes	-	no	480	-	yes	-	no	460	-	yes	-	no	460	-	yes	-
<i>z^{ef}</i>	Adjustable clear distance between armrest pads	yes	410	510	yes	-	yes	410	510	yes	-	yes	460	510	yes	-	yes	460	510	yes	-
	Fixed clear distance between armrest pads	no					no					no	460	510	no	-	no	460	-	yes	-
<i>p</i>	Height of armrests adjustable	yes	200	290	yes	100	yes	200	290	yes	100	yes	225	250	yes	50	yes	200	250	yes	-
	Height of armrests not adjustable	no					no					no	225	275	no	-	no	200	250	no	-



		Type Ax					Type A					Type B					Type C				
		Allow (-)	Min.	Max.	Allow (+)	Minimum range	Allow (-)	Min.	max.	Allow (+)	Minimum range	Allow (-)	min.	max.	Allow (+)	Minimum range	Allow (-)	min.	max.	Allow (+)	Minimum range
d	Seat pad width	no	400	-	yes	-	no	400	-	yes	-	no	400	-	yes	-	no	400	-	yes	-
c	Seat pad depth	no	380	-	yes	-	no	380	-	yes	-	no	380	-	yes	-	no	380	-	yes	-
h	Backrest height	no	360	-	yes	-	no	360	-	yes	-	no	360	-	yes	-	no	360	-	yes	-
j	Backrest width	no	360	-	yes	-	no	360	-	yes	-	no	360	-	yes	-	no	360	-	yes	-
k	Radius of backrest	no	400	-	yes	-	no	400	-	yes	-	no	400	-	yes	-	no	400	-	yes	-
n	Armrest length	no	150	-	yes	-	no	150	-	yes	-	no	150	-	yes	-	no	150	-	yes	-
o	Armrest width	no	50	-	yes	-	no	50	-	yes	-	no	40	-	yes	-	no	40	-	yes	-
s	Offset of the underframe	yes	-	415	no	-	yes	-	415	no	-	yes	-	415	no	-	yes	-	415	no	-

		Type Ax					Type A					Type B					Type C				
		Allow (-)	Min.	Max.	Allow (+)	Minimum range	Allow (-)	Min.	max.	Allow (+)	Minimum range	Allow (-)	min.	max.	Allow (+)	Minimum range	Allow (-)	min.	max.	Allow (+)	Minimum range

^a For tall office work chairs the seat height is determined as the vertical distance measured at the front of the seat, from the loaded seat to the floor or top of the foot support. The foot support shall have a minimum diameter of 20 mm or be flat.

^b For type Ax only, the range can be achieved e.g. by using a telescopic gas cylinder or by providing more than one gas cylinder

^c Sitting height is only applicable for chairs with seat pad angles less than 0° (rearwards slope).

^d The distance q shall be measured when the minimum usable armrest area template, 150 mm x 50 mm (Type Ax and Type A) or 150 mm x 40 mm (Type B and Type C), are parallel to the median plane (see 3.9) of the seat.

^e The gap shall be retained across the height adjustment range of the armrests for functional fit.

^f The clear distance z shall be measured when the minimum usable armrest area templates, 150 mm x 50 mm (Type Ax and Type A) or 150 mm x 40 mm (Type B and Type C), are parallel to the median plane of the seat.

64





Table 3—Angle requirements

		Table 3 — Angle requirements																			
		Dimensions in degrees																			
		Type Ax					Type A					Type B					Type C				
		Allow (-)	min	max	Allow (+)	Minimum range	Allow (-)	min	max	Allow (+)	Minimum range	Allow (-)	min	max	Allow (+)	Minimum range	Allow (-)	min	max	Allow (+)	Minimum range
y ^a	Angle between seat and back	no	90	-	yes	-	no	90	-	yes	-	no	90	-	yes	-	no	90	-	yes	-
l	Backrest inclination range	Minimum 15 degrees					Minimum 15 degrees					Minimum 15 degrees									
e ^b	Seat pad angle adjustable	yes	0	-	Yes	-	yes	0	-	Yes	-	yes	-2	-	Yes	-	Yes	-2	-	Yes	-
	Minimum adjustment range	5					5					5					5				
	Seat pad angle fixed	no					no					no					no				
a		As long as it is possible to achieve an angle of minimum 90° between seat pad and backrest, the requirement is fulfilled.																			
b		The adjustment range shall include the specified seat pad angle.																			

Table C.1 — dimensions for neck rests and headrests

		Dimensions in millimetres																			
		Type Ax					Type A					Type B					Type C				
		Allow (-)	min	max	Allow (+)	Minimum range	Allow (-)	min	max	Allow (+)	Minimum range	Allow (-)	min	max	Allow (+)	Minimum range	Allow (-)	min	max	Allow (+)	Minimum range
x	Height of adjustable neck rest or head rest	no	550	740	yes	-	no	550	740	yes	-	no	590	-	yes	-	no	590	-	yes	-
	Height of fixed neck rest or head rest	no					no					no					no				



Abbreviation: P=Pass; F=Fail; N/A = Not Applicable; N/T=Not Tested.

**Remark:**

1. The test results exclusively based on the submitted samples.
2. This report extracts from test report No. 64.190.25.1426.01-00, issued on 2025-05-19. Only update the applicant's name, address and Style No. information.
3. Specific requirement of test report as per clause 7.8.3 of CNAS-CL01-2018 or other accreditation scheme, such as: remark of subcontract information or on-site testing information.

Disclaimer Measurement Uncertainty:

Unless otherwise agreed upon, Pass or Fail verdicts are given based on the measured values without any considerations of measurement uncertainties.

Please note, every test method has a measurement uncertainty which has been evaluated by the laboratory according to ISO/IEC 17025 requirements.

By taking measurement uncertainties into account it might happen that measured values can neither be assessed as PASS nor as FAIL.

-End of Test Report-

